



32-Loch Gehäuse Speichenlänge
32-hole Hub-shell Spoke lengths

Laufradgröße / Wheel Size	Anzahl Kreuzungen / Number of Spoke Crosses	ERD*	32-Loch Speichenlänge / 32-hole Spoke lengths			
18"	1-X	341-343	128			
		344	130			
20"	1-X	372-373	142			
		374-377	144			
		378-381	146			
		382-385	148			
		386-389	150			
		390-394	152			
24"	1-X	472-476	192			
		477-480	194			
		481-484	196			
		485-489	198			
		490-493	200			
		494-497	202			
		498-501	204			
		502-503	206			
26"	2-X	516-519	226			
		520-523	228			
		524-527	230			
		528-531	232			
		532-535	234			
		536-539	236			
		540-543	238			
		544-547	240			
		548-551	242			
		552-555	244			
	650B	2-X	556-559	246		
			560-563	248		
			564-567	250		
			568-571	252		
			572-575	254		
			576-579	256		
			580-583	258		
			28"	2-X	584-587	260
					588-592	262
					593-596	264
597-600	266					
29"	2-X	601-604	268			
		605-608	270			
		609-612	272			
		613-616	274			
		617-620	276			
		621-624	278			
		625-628	280			
		629-632	282			

36-Loch Gehäuse Speichenlänge
36-hole Hub-shell Spoke lengths

Laufradgröße / Wheel Size	Anzahl Kreuzungen / Number of Spoke Crosses	ERD*	36-Loch Speichenlänge / 36-hole Spoke lengths			
18"	1-X	341-342	126			
		343-344	128			
20"	1-X	372-375	142			
		376-379	144			
		380-383	146			
		384-387	148			
		388-392	150			
		393-396	152			
24"	1-X	472-474	190			
		475-478	192			
		479-482	194			
		483-486	196			
		487-490	198			
		491-494	200			
		495-498	202			
		499-502	204			
		503	206			
		26"	2-X	516-517	222	
518-522	224					
523-526	226					
527-530	228					
531-534	230					
535-538	232					
539-542	234					
543-546	236					
547-550	238					
551-554	240					
650B	2-X		555-558	242		
			559-562	244		
			563-566	246		
			567-570	248		
			571-574	250		
			575-578	252		
			579-582	254		
			28"	2-X	583-586	256
					587-590	258
					591-594	260
595-598	262					
29"	2-X	599-602	264			
		603-607	266			
		608-611	268			
		612-615	270			
		616-619	272			
		620-623	274			
		624-627	276			
		628-631	278			

empfohlene Größe / recommended rim size



36-Loch ab Serien Nr.: silber/silver > 159293
36-hole from Serial-No.: schwarz/black > 159308
 rot/red > 155001

* ERD Messung - siehe Rohloff Handbuch 'Bestimmen des Felgeninnendurchmessers'.

* ERD Measurement - please refer to the Rohloff SPEEDHUB Owners Manual - 'Determining the effective rim diameter'.