

| | Key word | Page |
|----------|---|--|
| A | Advantages of the options | 38 |
| | Axle plate alignment | 64 |
| | Axle plates | 46 |
| | Axle ring - One-piece / Quick-change | 98, 104 |
| | Axle types | 24 |
| B | Bolt/tool info | 124 |
| | Brake disc - replacement | 60, 91 |
| | Brake discs / rotors | 37 |
| | Break-in period | 6 |
| C | Cable routing via the brake boss - Internal gear mech | 76 |
| | Cable routing via the chainstay - External gear mech | 80 |
| | Cable routing via the chainstay - Internal gear mech | 79 |
| | Cable routing via the top tube - External gear mech | 83 |
| | Carbon handlebars | 48 |
| | Chain guide - DH (accessory for downhill) | 45, 58 |
| | Chain guide - CC | 71 |
| | Chain tensioner - DH (accessory for downhill) | 45, 68, 69 |
| | Chain tensioner - mounting | 70 |
| | Chain tensioner spring - changing | 109 |
| | Chainguard enclosed | 48 |
| | Chainring - two chainrings | 45, 47 |
| | Cleaning the Rohloff SPEEDHUB 500/14 | 7 |
| | Colors | 33 |
| | Comparison - Derailleur gears and Rohloff SPEEDHUB 500/14 | 21 |
| | Comparison to derailleur gears | 22 |
| | Components that we recommend | 45 |
| | Cranks, Crankset | 45, 57 |
| | D | Distance travelled per crank revolution (20", 26" and 28") |
| E | Emergency repairs | 10 |
| | External gear mech - grub screw | 129 |
| | External gear mech - mounting | 32, 93 |
| | External gear mech - OEM / OEM2 / long torque arm | 63 |
| F | Failure Diagnosis | 119 |
| | Filling with oil | 84 |
| | Frame mounted gear box | 47 |
| | Frame types - OEM / OEM2 / long torque arm | 27-29 |
| | Gear display | 83 |
| G | Gear mech - replacement | 92 |
| | Gear unit - installation - removal | 112, 111 |
| | Grub screw of the External gear mech | 129 |
| | Guarantee information | 1, 128 |
| | Hub cable - replacement | 97 |
| H | Hub seal - replacement | 114 |
| | Index | 132 |
| I | Inner rim diameter - calculating | 44 |
| | Internal gear mech | 31 |
| | Internal gear mech - via brake boss / via chainstay | 61, 62 |
| | Long torque arm | 56 |
| M | Maintenance and care | 7, 8, 89 |
| | Mechanical efficiency - comparsion | 18 |
| | Model codes - explanation | 33 |
| | Model variations | 39 |

| | Key word | Page | |
|---|---|--|--------|
| N | Noises | 6 | |
| | Notices | 130 | |
| O | OEM axle plate | 67 | |
| | OEM2 - mounting with a support bolt / SPEEDBONE | 59 | |
| | OEM2 axle plate | 67 | |
| | Oil change | 7, 87 | |
| | One-piece axle ring - removal | 92 | |
| | Options | 38 | |
| P | Package contents - checking | 51 | |
| | Particular components | 45, 46, 47 | |
| | Pushing the bike | 6 | |
| Q | Quick-change axle ring - removal | 92 | |
| R | Racing bike / drop handlebars | 46 | |
| | Reference to Serial N° | 128 | |
| | Removal of the wheel from the frame | 13 | |
| | Replacing the gear unit | 92 | |
| | Reversing / Replacing of the sprocket | 90 | |
| | Riding noises | 6 | |
| | Rims | 46 | |
| | Rubber grip - replacement | 110 | |
| | S | Safety information | 3 |
| | | Schlumpf Speed-drive, High Speed-drive | 47 |
| | | Securing to the frame | 23-30 |
| | | Serial N° - Pointers | 128 |
| | | Service procedures | 96 |
| Shifter - mounting | | 73 | |
| Shifter cables | | 75 | |
| Shifting gears | | 5 | |
| Small parts bag - checking the contents | | 53 | |
| Small wheels | | 47 | |
| Smallest permitted sprocket ratios | | 19 | |
| Special applications | | 47, 48 | |
| SPEEDBONE | | 46 | |
| Spoke length - calculating | | 42, 43 | |
| Spokes | | 46 | |
| Sprocket ratios - smallest | | 19 | |
| Sprocket reversing/replacement | | 90 | |
| Sprockets | 45 | | |
| Stand - axle mounted | 47 | | |
| T | Tandem use | 47 | |
| | Technical data | 17, 127 | |
| | Tools and Bolts / Tools for the tour | 124, 9 | |
| | Torque securing | 25 | |
| | Tour info | 9 | |
| | Trailer use | 47 | |
| | Transport - Info for the tour | 9 | |
| | Trouble shooting | 119 | |
| | Twist shifter - mounting | 73 | |
| | W | Warranty information | 1, 128 |
| Wearable parts | | 6 | |
| Weight comparison | | 18 | |
| Wheel installation | | 14 | |

| | |
|--|--------|
| Modular system | 23 |
| Mounting (CC / TS versions) with a long torque arm | 65, 66 |
| Mounting necessities OEM2 | 30 |
| Mounting processes | 49 |

| | |
|--|-----|
| Wheel lacing for rims with a European spoke hole pattern | 125 |
| Wheel lacing for rims with a French spoke hole pattern | 126 |
| Wheel removal (internal, external gear mech) | 11 |
| Wheel stability | 41 |
| Wheel lacing | 55 |

KOPIE