

Einbaumaß (135mm, 142mm)  
 Frame spacing (135mm, 142mm)



**32-Loch Gehäuse Speichenlänge**  
**32-hole Hub-shell Spoke lengths**

Laufradgröße / Wheel Size	Anzahl Kreuzungen / Number of Spoke Crosses	ERD*	32-Loch Speichenlänge / 32-hole Spoke lengths		
18"	1-X	341-343	128		
		344	130		
20"	1-X	372-373	142		
		374-377	144		
		378-381	146		
		382-385	148		
		386-389	150		
		390-394	152		
24"	1-X	472-476	192		
		477-480	194		
		481-484	196		
		485-489	198		
		490-493	200		
		494-497	202		
		498-501	204		
		502-503	206		
650B	2-X	516-519	226		
		520-523	228		
		524-527	230		
		528-531	232		
		532-535	234		
		536-539	236		
		540-543	238		
		544-547	240		
		548-551	242		
		552-555	244		
	2-X	556-559	246		
		560-563	248		
		564-567	250		
		568-571	252		
		572-575	254		
		576-579	256		
		580-583	258		
		28"	2-X	584-587	260
				588-592	262
				593-596	264
597-600	266				
601-604	268				
605-608	270				
29"	2-X	609-612	272		
		613-616	274		
		617-620	276		
		621-624	278		
		625-628	280		
		629-632	282		

**36-Loch Gehäuse Speichenlänge**  
**36-hole Hub-shell Spoke lengths**

Laufradgröße / Wheel Size	Anzahl Kreuzungen / Number of Spoke Crosses	ERD*	36-Loch Speichenlänge / 36-hole Spoke lengths		
18"	1-X	341-342	126		
		343-344	128		
20"	1-X	372-375	142		
		376-379	144		
		380-383	146		
		384-387	148		
		388-392	150		
		393-396	152		
24"	1-X	472-474	190		
		475-478	192		
		479-482	194		
		483-486	196		
		487-490	198		
		491-494	200		
		495-498	202		
		499-502	204		
		503	206		
		650B	2-X	516-517	222
518-522	224				
523-526	226				
527-530	228				
531-534	230				
535-538	232				
539-542	234				
543-546	236				
547-550	238				
551-554	240				
2-X	555-558		242		
	559-562		244		
	563-566		246		
	567-570		248		
	571-574		250		
	575-578		252		
	579-582		254		
	28"		2-X	583-586	256
				587-590	258
				591-594	260
595-598		262			
599-602		264			
603-607		266			
29"	2-X	608-611	268		
		612-615	270		
		616-619	272		
		620-623	274		
		624-627	276		
		628-631	278		

empfohlene Größe / recommended rim size



36-Loch ab Serien Nr.: silber/silver > 159293  
 36-hole from Serial-No.: schwarz/black > 159308  
 rot/red > 155001

\* ERD Messung - siehe Rohloff Handbuch 'Bestimmen des Felgeninnendurchmessers'.

\* ERD Measurement - please refer to the Rohloff SPEEDHUB Owners Manual - 'Determining the effective rim diameter'.