

14. Different hub types and their assembly instructions

The minimal requirements laid down by the Rohloff AG must be met when mounting a *Rohloff SPEEDHUB 500/14* OEM2 version in connection with a support bolt, Speedbone, Monkeybone (mounted to the disc brake mount) or M5 bolt adapter (for luggage rack/fender mount tapped hole). Likewise, when mounting a *Rohloff SPEEDHUB 500/14* PM version with a PM Bone mounted to a Postmount direct brake mount.

Faultless materials and first grade workmanship must be guaranteed.

Mounting a *Rohloff SPEEDHUB 500/14* with an OEM2/ PM axleplate into an eBike or Tandem is only permitted when using a Speedbone, Monkeybone or PM Bone.

Release from liability – ***Speedbone*** or ***Monkeybone*** (OEM2 Axleplate)
PM-Bone (PM Axleplate)

Manufacturer:

I hereby declare that the OEM2 Axleplate with or without either a Speedbone, Monkeybone, or M5 adapter bolt, and/or the PM Axleplate with PM Bone, is fitted to the following bicycles:

I herewith release the company 'Rohloff AG' from product liability concerning possible arising damages to the disc brake mount of the frame, as well as from resulting damages or injuries to persons or items caused by the use of the OEM2/SPEEDBONE/Monkeybone/M5 Adapter or PM/PM Bone version.

Date, Signature (responsible)

Stamp