


32-Loch Gehäuse Speichenlänge
32-spokehole hubshell spokelength

Laufradgröße / Wheel Size	Anzahl Kreuzungen / Number of Spoke Crosses	ERD*	32-Loch Speichenlänge / 32-hole Spoke lengths 7mm Offset	32-Loch Speichenlänge / 32-hole Spoke lengths 12.5mm Offset	32-Loch Speichenlänge / 32-hole Spoke lengths 20mm Offset	
26"	2-X	516-519	228	228	226	
		520-523	230	230	228	
		524-527	232	232	230	
		528-531	234	234	232	
		532-535	236	236	234	
		536-539	238	238	236	
		540-544	240	240	238	
		545-548	242	242	240	
	650B	2-X	549-552	244	244	242
			553-556	246	246	244
			557-560	248	248	246
			561-564	250	248-250	248
			565-568	252	250-252	250
			569-572	254	252-254	252
			573-576	256	254-256	254
			577-580	258	256-258	256
29"	2-X	581-584	260	258-260	258	
		585-588	262	X	X	
		589-592	264	X	X	
		593-596	266	X	X	
		597-600	268	X	X	
		601-604	270	X	X	
		605-608	272	X	X	

* ERD Messung - siehe Rohloff Handbuch 'Bestimmen des Felgeninnendurchmessers'.

* ERD Measurement - please refer to the Rohloff SPEEDHUB Owners Manual.

('Determining the effective rim diameter')

V04-2020 - Technische Änderungen vorbehalten. Rohloff reserve the right to change technical specifications without prior warning.